



# KBS RustSeal

## Safety Data Sheet

Revision date: 12/19/2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : KBS RustSeal  
Product form : Mixture  
Other means of identification : RustSeal RS

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Rust preventive. Corrosion sealing coating.

#### 1.3. Details of the supplier of the safety data sheet

Advanced Protective Technologies  
1101 Cumberland Xing #180  
Valparaiso, IN 46383  
Phone: 1 (219) 263-0073

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
Resp. Sens. 1 H334  
Skin Sens. 1 H317  
Carc. 2 H351  
Repr. 1B H360  
STOT SE 3 H335  
STOT RE 1 H372

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335 - May cause respiratory irritation  
H351 - Suspected of causing cancer  
H360 - May damage fertility or the unborn child  
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe fume, vapors  
P264 - Wash hands, forearms and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear protective clothing, protective gloves, eye protection  
P284 - [In case of inadequate ventilation] wear respiratory protection  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

# KBS RustSeal

## Safety Data Sheet

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308 + P313 - If exposed or concerned: Get medical advice/attention  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see first aid instructions on this label)  
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention  
P337 + P313 - If eye irritation persists: Get medical advice/attention  
P342 + P311 - If experiencing respiratory symptoms: Call a poison center/doctor/...  
P362 - Take off contaminated clothing and wash before reuse  
P370 + P378 - In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up  
P501 - Dispose of contents/container to licensed waste handling facility

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, methyloxirane and 1,2-propanediol	(CAS No) 67815-87-6	60 - 100
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	40 - 70
4-4'-Methylenediphenyl diisocyanate	(CAS No) 101-68-8	10 - 30
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	10 - 30
Isocyanic acid, polymethylenepolyphenylene ester	(CAS No) 9016-87-9	5 - 10
Benzene, 1,1'-methylenebis[isocyanato-	(CAS No) 26447-40-5	1 - 5
Solvent naphtha, petroleum, medium aliphatic	(CAS No) 64742-88-7	0 - 5
Stoddard solvent	(CAS No) 8052-41-3	0 - 5
Ethylbenzene	(CAS No) 100-41-4	0 - 1
Diisobutyl ketone	(CAS No) 108-83-8	0.1 - 1
Fatty acids, tall-oil, compounds with oleylamine	(CAS No) 85711-55-3	0 - 1
1-Methyl-2-pyrrolidone	(CAS No) 872-50-4	0 - 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

First-aid measures after skin contact : IF ON SKIN (or clothing), remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation persists, call a physician.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : IF SWALLOWED: Immediately give large amounts of water. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Irritating to eyes and skin. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

Symptoms/injuries after inhalation : May cause headache, nausea and irritation of respiratory tract.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes eye irritation.

Symptoms/injuries after ingestion : May cause gastrointestinal irritation, nausea, vomiting, and diarrhea if swallowed.

Chronic symptoms : May cause damage to target organs. May cause cancer. May damage fertility. May damage the unborn child. Skin sensitization.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# KBS RustSeal

## Safety Data Sheet

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide.

Unsuitable extinguishing media : Water.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Explosion hazard : Solvent vapors may form explosive mixtures with air.

Reactivity : May react violently with incompatible materials.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Eliminate every possible source of ignition. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Take up liquid spill into inert absorbent material, e.g.: sand, earth, vermiculite. Sweep or shovel spills into appropriate container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Use appropriate personal protection equipment (PPE). Keep away from sources of ignition - No smoking. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed in a cool, dry, and well-ventilated place. Store product between 5 and 35°C (41 and 95°F).

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, methyloxirane and 1,2-propanediol (67815-87-6)</b>	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established

<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established

# KBS RustSeal

## Safety Data Sheet

<b>4-4'-Methylenediphenyl diisocyanate (101-68-8)</b>	
ACGIH TWA (ppm)	0.005 ppm (listed under Methylene bisphenyl isocyanate (MDI))
OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
OSHA PEL (Ceiling) (ppm)	0.02 ppm
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established
<b>Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)</b>	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established
<b>Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)</b>	
Remark (ACGIH)	OELs not established
OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
OSHA PEL (Ceiling) (ppm)	0.02 ppm
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established
<b>Stoddard solvent (8052-41-3)</b>	
ACGIH TWA (ppm)	100 ppm
Remark (ACGIH)	Eye, skin, & kidney dam;
OSHA PEL (TWA) (mg/m <sup>3</sup> )	2900 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	500 ppm
<b>Ethylbenzene (100-41-4)</b>	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	125 ppm
<b>Diisobutyl ketone (108-83-8)</b>	
ACGIH TWA (ppm)	25 ppm
Remark (ACGIH)	URT & eye irr
OSHA PEL (TWA) (mg/m <sup>3</sup> )	290 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	50 ppm
<b>Fatty acids, tall-oil, compounds with oleylamine (85711-55-3)</b>	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established

### 8.2. Exposure controls

Appropriate engineering controls

: Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Protective goggles. Protective clothing.



# KBS RustSeal

## Safety Data Sheet

Hand protection	: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.
Eye protection	: Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.
Skin and body protection	: Avoid skin contact by wearing chemically resistant suit protecting against chemicals, chemically resistant gloves, a chemically resistant apron and other protective equipment depending upon conditions of use. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Inspect gloves and contact equipment for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
Respiratory protection	: Where excessive vapor, mist, or dust may result, use NIOSH approved respiratory protection equipment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Color specified on label.
Odor	: Solvent.
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: -5 °C (23°F)
Boiling point	: 100 °C (212°F)
Flash point	: 40 °C (104°F)
Auto-ignition temperature	: 220 °C (248°F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 1.09
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

May react violently with incompatible materials.

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

Contact with moisture, other materials that react with isocyanates, or temperatures above 350°F (177°C) may cause polymerization.

#### 10.4. Conditions to avoid

Heat. Direct sunlight. Moisture.

#### 10.5. Incompatible materials

Water, amines, strong bases, alcohols. Copper alloys. Amides, phenols, mercaptans, urethanes, ureas and surface active compounds.

#### 10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. smoke and irritating fumes. Isocyanate. Other undetermined compounds.

# KBS RustSeal

## Safety Data Sheet

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h
LC50 inhalation rat (ppm)	3400 ppm/4h

<b>4-4'-Methylenediphenyl diisocyanate (101-68-8)</b>	
LD50 oral rat	9200 mg/kg
LC50 inhalation rat (mg/l)	178 mg/m <sup>3</sup>

<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
LD50 oral rat	3400 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	18 g/m <sup>3</sup> 4h

<b>Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)</b>	
LC50 inhalation rat (mg/l)	0.49 mg/l/4h 4 h

<b>Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)</b>	
LD50 oral rat	> 7400 mg/kg (Source: IUCLID)
LD50 dermal rabbit	> 6200 mg/kg (Source: IUCLID)
LC50 inhalation rat (mg/l)	0.369 mg/l/4h (Source: IUCLID)

<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h

<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h

<b>Diisobutyl ketone (108-83-8)</b>	
LD50 oral rat	5750 mg/kg
LD50 dermal rabbit	16 g/kg
LC50 inhalation rat (ppm)	> 2300 ppm/4h

<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
LD50 oral rat	3598 mg/kg
LD50 dermal rat	2500 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	3.1 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
 Serious eye damage/irritation : Causes serious eye irritation.  
 Respiratory or skin sensitization : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Suspected of causing cancer.

<b>4-4'-Methylenediphenyl diisocyanate (101-68-8)</b>	
IARC group	3 - Not classifiable

<b>Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)</b>	
IARC group	3 - Not classifiable

<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

# KBS RustSeal

## Safety Data Sheet

Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause headache, nausea and irritation of respiratory tract.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: May cause gastrointestinal irritation, nausea, vomiting, and diarrhea if swallowed.
Chronic symptoms	: May cause damage to target organs. May cause cancer. May damage fertility. May damage the unborn child. Skin sensitization.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

### SECTION 14: Transport information

In accordance with DOT

As packaged this material can be shipped as a "Consumer Commodity ORM-D" Exemption.

#### Additional information

Other information : No supplementary information available.

#### Transport by sea

UN-No. (IMDG) : UN1263

Proper Shipping Name (IMDG) : Paint

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : LTD QTY

#### Air transport

UN-No.(IATA) : UN1263

Proper Shipping Name (IATA) : Paint

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : III - Minor Danger

Instruction "cargo" (ICAO) : 30 L

Instruction "passenger" (ICAO) : 1 L

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### KBS RustSeal

All chemical substances in this product are listed in the EPA (Environmental Protection Agency) TSCA (Toxic Substances Control Act) Inventory

# KBS RustSeal

## Safety Data Sheet

<b>KBS RustSeal</b>	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
<b>Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, methyloxirane and 1,2-propanediol (67815-87-6)</b>	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
<b>4-4'-Methylenediphenyl diisocyanate (101-68-8)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 313 - Emission Reporting	1 % de minimis concentration (listed under Chemical Category N120, Diisocyanates)
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1 %
<b>Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
SARA Section 313 - Emission Reporting	1 % de minimis concentration (listed under Chemical Category N120, Diisocyanates)
<b>Aluminum (7429-90-5)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1 %
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	100 lb
SARA Section 313 - Emission Reporting	1 %
<b>Ethylbenzene (100-41-4)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
<b>n-Butyl acetate (123-86-4)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb (listed under Butyl acetate)
<b>Copper (7440-50-8)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)
SARA Section 313 - Emission Reporting	1 %
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1 % de minimis concentration
<b>Cumene (98-82-8)</b>	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
SARA Section 313 - Emission Reporting	1 %



# KBS RustSeal

## Safety Data Sheet

### 15.2. International regulations

#### CANADA

No additional information available

### 15.3. US State regulations

#### California Proposition 65

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

<b>Titanium dioxide (13463-67-7)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
<b>Carbon black (1333-86-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
<b>Ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			
<b>Cumene (98-82-8)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
<b>4-4'-Methylenediphenyl diisocyanate (101-68-8)</b>				
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
<b>Titanium dioxide (13463-67-7)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
<b>Iron oxide (Fe2O3) (1309-37-1)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List				

# KBS RustSeal

## Safety Data Sheet

### Aluminum (7429-90-5)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### Xylenes (o-, m-, p- isomers) (1330-20-7)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### Carbon black (1333-86-4)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Massachusetts - Right To Know List

### Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List

### Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

### Silica, amorphous (7631-86-9)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Stoddard solvent (8052-41-3)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Ethylbenzene (100-41-4)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### Diisobutyl ketone (108-83-8)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List

### n-Butyl acetate (123-86-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### Copper (7440-50-8)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### 1-Methyl-2-pyrrolidone (872-50-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### Cumene (98-82-8)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

## SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.  
Revision date : 12/19/2018  
Other information : Author: EKW.


# KBS RustSeal

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
- NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



### HMIS III Rating

- Health : 2\*
- Flammability : 2
- Physical : 1
- Personal Protection :

KBS Coatings believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of KBS Coatings, KBS Coatings expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.